This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

XRPX Acc No: N99-454776

Current supply timing control mechanism for fuel cut-off valve for compressed natural gas fired engine in vehicles - determines current supply time, based on pressure difference between front and rear sides of fuel shut off valve

Patent Assignee: AISAN KOGYO KK (AISA); TOYOTA JIDOSHA KK (TOYT) Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
JP 11270412 A 19991005 JP 9874300 A 19980323 199953 B

Priority Applications (No Type Date): JP 9874300 A 19980323

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

JP 11270412 A 9 F02M-021/02

Abstract (Basic): JP 11270412 A

NOVELTY - A control unit (18) detects the pressure difference between the front and rear sides of a fuel shut off valve (13). The control unit determines current supply time based on comparison of pressure difference with a predefined value. The current supply time, when pressure difference is greater than the predetermined value, is larger than that when pressure difference is lesser. DETAILED DESCRIPTION - The pressure at the front and rear sides of the fuel shut off valve is determined by the pressure sensors (16,17). The control unit supplies the holding current to the valve after the supply of the initial current.

USE - For shut off valve of compressed natural gas fired engine in vehicle.

ADVANTAGE - Since the control unit determines the current supply time to the fuel shut off valve, based on the pressure difference between the front and rear sides of the valve, power consumption is controlled optimally, and the durability and efficiency of the fuel shut off valve is improved. DESCRIPTION OF DRAWING(S) - The figure shows the schematic block diagram of the current supply timing control mechanism for fuel shut off valve of fuel supply system. (13) Fuel shut off valve; (16,17) Pressure sensors; (18) Control unit.

Dwg.1/15

Title Terms: CURRENT; SUPPLY; TIME; CONTROL; MECHANISM; FUEL; CUT; VALVE; COMPRESS; NATURAL; GAS; FIRE; ENGINE; VEHICLE; DETERMINE; CURRENT; SUPPLY; TIME; BASED; PRESSURE; DIFFER; FRONT; REAR; SIDE; FUEL; SHUT; VALVE

Derwent Class: Q52; Q53; X22

International Patent Class (Main): F02M-021/02

International Patent Class (Additional): F02D-019/06; F02D-041/02;

F02M-037/00

File Segment: EPI; EngPI